

Setting New Standards Worldwide
Turf Industry Leaders in Service and Innovation





WE'RE COMMITTED TO IMPROVING YOUR HARVEST.



The Brouwer 2200 Harvester on a John Deere 5065E is a workhorse that puts the best quality piece of Turf on the Conveyor that is possible. The Outer Frame surrounds a rugged floating cutting head that has easy pitch and roller adjustments to get the perfect cut. The low front pivot point and heavy pressure on the front roller makes sure that the head follows every contour that it encounters. The Pivot Bearing insures rapid action back and forth to provide an even cut from side to side, even cutting through curves. The heavy duty construction makes this a perfect choice in the hardest conditions (stones included) or in Tender Turf where gentle handling is required.

Specifications:

WIDTH OF CUT

16" (406mm) 18" (457mm) 21" (533mm) 23" (584mm) 24" (610mm)

LENGTH OF CUT

24" (610 mm) to 100" (2540 mm)

PERFORMANCE

1500 sq. yd. (1260 m/sq.) per hour.

THICKNESS OF CUT

Power Adjustable to 2 1/4" (57 mm)

OPERATING DIMENSIONS

L.176 in.(4470 mm.) W. 120 in.(3048 mm.) H. 104 in. (2641 mm.)

WEIGHT

3610 lbs. (1637 kg) (Havester weight may vary on spec)



KESMAC INC.

TEL: 905-476-6222 • 1-888-341-5113 FAX: 905-476-6744 US Parts TEL: 1-800-314-1008

23324 Woodbine Avenue, Keswick, Ontario L4P 3E9 email: info@kesmac.com • www.brouwerturf.com





Features:

- Full Floating Cutter Head, with hydraulic depth control, floats for reliable sod thickness in all ground conditions
- Manual Hydraulic Controls to operate the harvester functions
- · Available in Roll or Slab
- · Independently mounted Curved or Cross Conveyor
- · No waste: cuts close to pipes, fences and ditches
- · Easy entry with rear piling door for quick service
- · Conveyor mat is gentle on turf and long on durability
- Full canopy with flashing signal and halogen work lights
- Main beam forward design for better weight distribution
- Stored weights can be added to cutter head to adapt to various conditions

Options:

- 4 Wheel Drive
- · Brush attachment
- · Adjustable piling wall for smaller pallets
- Piling wall extensions
- · Auto-steer with fine micro adjustment
- · Independent cross conveyor for Roll Unit
- Hydraulic Variable Speed Roll Up
- · Selection of starter trays
- Slabbing attachment; independent hydraulic curved conveyor with rollers/brushes, scrapers, and dirt deflector
- · Secondary standing platform Slabs
- · Coulter side blades
- Fold down pallet carrier
- Mechanical Counter
- · 10 in. Ground Roller
- · Water cooler